

Appl. No. 10/709,198
Amdt. dated August 30, 2005
Reply to Office action of June 14, 2005

Amendments to the Claims:

Claim 1. (original) A variable gain amplifier, comprising:

an amplifying stage for generating an output voltage according to an input voltage; and
a variable gain stage for adjusting a voltage gain of the amplifying stage according to at
5 least a controlling voltage;
wherein the voltage gain is a simple exponential function, and the value of the simple
exponential function is determined by the controlling voltage.

Claim 2. (original) The variable gain amplifier of claim 1, wherein the simple exponential
10 function comprises a function which raises a base to the power of an argument, without
an addition operation or a subtraction operation with a constant being performed on the
function.

Claim 3. (original) The variable gain amplifier of claim 1, wherein the at least one
15 controlling voltage comprises a first controlling voltage and a second controlling
voltage, and the value of the simple exponential function is determined by the
difference between the first and the second controlling voltages.

Claim 4. (original) The variable gain amplifier of claim 3, wherein the variable gain stage is
20 a transconductance amplifier for generating a gain current according to the difference
between the first and the second controlling voltages.

Claim 5. (original) The variable gain amplifier of claim 4, wherein the variable gain stage
comprises:
25 a first transistor coupled to the first controlling voltage;
a second transistor coupled to the second controlling voltage;
a first current source coupled to the emitter of the first and the second transistors for

Appl. No. 10/709,198
Amdt. dated August 30, 2005
Reply to Office action of June 14, 2005

providing a first current; and

a second current source for generating the gain current, wherein the value of the gain current is determined by the first current and the difference between the first and the second controlling voltages.

5

Claim 6. (original) The variable gain amplifier of claim 5, wherein the variable gain stage further comprises:

a first resistor coupled between the collector of the first transistor and the second current source; and

10 a second resistor coupled between the collector of the second transistor and the second current source.

Claim 7. (original) The variable gain amplifier of claim 5, wherein the amplifying stage comprises:

15 an input unit coupled to the input voltage for generating an input current according to the input voltage;

a current transforming unit for generating a second current according to the gain current; and

20 a transresistance amplifying unit for generating the output voltage, wherein the value of the output voltage is determined by the input current and the second current.

Claim 8. (original) The variable gain amplifier of claim 7, wherein the input unit comprises an input transistor coupled to the input voltage for generating the input current according to the input voltage.

25

Claim 9. (original) The variable gain amplifier of claim 7, wherein the current transforming unit comprises:

a third transistor, the collector of the third transistor being coupled to the base of the

Appl. No. 10/709,198
Amdt. dated August 30, 2005
Reply to Office action of June 14, 2005

third transistor;
a fourth transistor;
a third current source coupled to the emitter of the third and the fourth transistors for
providing a third current; and
5 a fourth current source for generating the second current;
whereby the ratio between the third current and the first current is substantially
equivalent to the ratio between the second current and the gain current.

Claim 10. (original) The variable gain amplifier of claim 9, wherein the current transforming
10 unit further comprises:
a third resistor coupled between the collector of the third transistor and the fourth
current source; and
a fourth resistor coupled between the collector of the fourth transistor and the fourth
current source.

15 Claim 11. (original) The variable gain amplifier of claim 9, wherein the transresistance
amplifying unit comprises:
a fifth transistor, the base and the collector of the fifth transistor being coupled to the
base of the fourth transistor;
20 a sixth transistor, the base of the sixth transistor being coupled to the base of the third
transistor;
a seventh transistor, the base and the collector of the seventh transistor being coupled to
the emitter of the fifth and the sixth transistors;
a fifth current source coupled to the input unit and the collector of the fifth transistor for
25 providing a fifth current; and
an output resistor coupled to the collector of the sixth transistor for generating the
output voltage.

Appl. No. 10/709,198
Amdt. dated August 30, 2005
Reply to Office action of June 14, 2005

Claim 12. (currently amended) The variable gain amplifier of claim 3, wherein the voltage gain ~~can be~~ is expressed as $C1 \times \exp(C2(V1-V2))$, wherein both C1 and C2 are constant values, V1 is the first controlling voltage, and V2 is the second controlling voltage.

5 Claim 13. (original) The variable gain amplifier of claim 1, wherein the variable gain amplifier is the half-circuit of a differential amplifier.

Claim 14. (new) A variable gain amplifier, comprising:

10 an amplifying stage for generating an output voltage according to an input voltage;
and
a variable gain stage for adjusting a voltage gain of the amplifying stage according to at least a controlling voltage;
wherein the voltage gain changes linearly in decibel in response to the controlling voltage.

15

Claim 15. (new) The variable gain amplifier of claim 14, wherein the voltage gain changes linearly in decibel with respect to a simple exponential function, and the value of the simple exponential function is determined by the controlling voltage.

20 Claim 16. (new) The variable gain amplifier of claim 15, wherein the simple exponential function comprises a function which raises a base to the power of an argument, without an addition operation or a subtraction operation with a constant being performed on the function.

25 Claim 17. (new) The variable gain amplifier of claim 14, wherein the at least one controlling voltage comprises a first controlling voltage and a second controlling voltage, and the voltage gain changes linearly in decibel according to the difference between the first and the second controlling voltages.

Appl. No. 10/709,198
Amdt. dated August 30, 2005
Reply to Office action of June 14, 2005

Claim 18. (new) The variable gain amplifier of claim 17, wherein the variable gain stage is a transconductance amplifier for generating a gain current according to the difference between the first and the second controlling voltages.

5

Claim 19. (new) The variable gain amplifier of claim 18, wherein the variable gain stage comprises:

- a first transistor coupled to the first controlling voltage;
- a second transistor coupled to the second controlling voltage;
- 10 a first current source coupled to the emitter of the first and the second transistors for providing a first current; and
- a second current source for generating the gain current, wherein the value of the gain current is determined by the first current and the difference between the first and the second controlling voltages.

15

Claim 20. (new) The variable gain amplifier of claim 19, wherein the variable gain stage further comprises:

- a first resistor coupled between the collector of the first transistor and the second current source; and
- 20 a second resistor coupled between the collector of the second transistor and the second current source.

Claim 21. (new) The variable gain amplifier of claim 18, wherein the amplifying stage comprises:

- 25 an input unit coupled to the input voltage for generating an input current according to the input voltage;
- a current transforming unit for generating a second current according to the gain current; and

BEST AVAILABLE COPY

Appl. No. 10/709,198
Amdt. dated August 30, 2005
Reply to Office action of June 14, 2005

a fifth transistor, the base and the collector of the fifth transistor being coupled to
the base of the fourth transistor;
a sixth transistor, the base of the sixth transistor being coupled to the base of the
third transistor;
5 a seventh transistor, the base and the collector of the seventh transistor being
coupled to the emitter of the fifth and the sixth transistors;
a fifth current source coupled to the input unit and the collector of the fifth transistor
for providing a fifth current; and
an output resistor coupled to the collector of the sixth transistor for generating the
10 output voltage.

Claim 26. (new) The variable gain amplifier of claim 17, wherein the voltage gain is
expressed as $C1 \times \exp(C2(V1-V2))$, wherein both C1 and C2 are constant values, V1
is the first controlling voltage, and V2 is the second controlling voltage.

15

Claim 27. (new) The variable gain amplifier of claim 1, wherein the variable gain
amplifier is the half-circuit of a differential amplifier.